

EVEREST**Material list**

Marking of components	Material / product name	Technical data/ Dimesion weight / strength	Producer
Attachment loops	Nylon	5,9 g/m / breaking strength 90kg / 10mm spreads	Kolon Industrial Co. Korea
Accelerator lock	Brummelhook		Gin Gliders Korea
brake attachements	Nylon	5,9 g/m / breaking strength 90kg / 10mm spreads	Kolon Industrial Co. Korea
brake handhold	High Tanacity Poliester Yarn 22mm	16 g/m / 200 kg breaking strength	Gin Gliders Korea
brake handhold attachement	High Tanacity Poliester Yarn 22mm	16 g/m / 200 kg breaking strength	Gin Gliders Korea
brake handhold fixation	Velcro		Gin Gliders Korea
Brake main line LIROS DC200	Dynema Lines	1,8mm / 200daN	LIROS, Rosenberger Tauwerke, Germany
Lines: Look at Lineconfiguration	Liros / Edelrid	look at lineconfiguration	Rosenberger Tauwerke / EDELRID-Germany
Top	Skytex 38 // Dokdo 10	38 g/m ² // 24g/m ² PA 6.6	Porcher, NCV, France; Dominico Tex, Korea
Bottom	Dokdo 10	24g/m ² PA 6.6	Dominico Tex, Korea
Rips, Profile	Skytex 27 hard finish	27 g/m ² , PA 6.6 HT, HF	Porcher, NCV, France
Profilnose reinforcement	PPN - Nylon	2,2mm / 2,6mm Ø	Gin Gliders Korea
Riser	High Tanacity Keflar 6mm	16 g/m / 900 kg breaking strength	LIROS, Rosenberger Tauwerke, Germany
Reinforcement powit point A/B/C/D	G 150 Dacron	150 g/m ²	Gin Gliders Korea
sewing thread canopy	High Tanacity Poliester Yarn 150D/2	0,05 g/m ² / 2,9 kg breaking strength	Amann & Söhne GmbH, Germany
sewing thread line	High Tanacity Poliester Yarn 150D/3	0,083 g/m ² / 3,2 kg breaking strength	Amann & Söhne GmbH, Germany